



For wire collated
BDC nails

CE

BeA Pneumatic Nailer 572 DCC

For nails of $\varnothing 2,1 - 2,4$ mm in the lengths of 30 - 55 mm

- Extremely powerful and sturdy
- 360° adjustable exhaust
- Integrated sound absorption
- Ergonomic handgrip, insulated against cold
- Metal coil guide plate
- Translucent dust and dirt protection
- Contact actuation

Applications

Production of pallets , crates and wooden boxes, interior fittings, drywalls



BeA 572 DCC

Technical Data



Article no.	12100673
EAN code	4045759061441
Magazine type	Top loader
Weight	2,55 kg
Measurements, mm	L 293, H 270, W 130
Safety system	Contact actuation
Fastener type	Nail type BDC
Magazine capacity	1 coil
Operating pressure	5 - 8 bar
Max. operating pressure	8 bar
Air consumption / operation	1,5-2,0 liter / 6 bar
Inner hose diameter	Ø 9 mm LW recommended
Emission sound pressure level at workstation	$L_{pA, 1s, d} = 88$ dB
Single shot emission sound pressure level	$L_{WA, 1s, d} = 95$ dB
Vibration level as per ISO 8662-11 is	2,86 m/s^2 .
Accessories	Operating instructions, spare parts list, service instructions, allen wrench


Coil nails BDC

BDC nails = wire welded coil nails

Length	30 - 55 mm
Diameter	2,1 - 2,4 mm

Material	BK = steel, bright
	NK = steel, electro galvanized
	RF = stainless steel, comparable with material 1.4301
	NR = stainless steel, comparable with material 1.4401
Surface properties	FV = steel, hot dipped galvanized
	Smooth
	Ring shank
Head type	Screw shank
	Flat head
	Dome head
	PZ head
	TX head

Further types available on request, nails conform to DIN 1052 as well as EN 14592 (Eurocode 5)



BDC: 30 - 55 mm

Joh. Friedrich Behrens AG
Industrielle
Befestigungssysteme
Bogenstraße 43 - 45 22926
Ahrensburg Germany

Further information:
Tel: + 49(0) 41 02 78 - 444 Fax
+ 49 (0) 41 02 78 - 270

Email: info@bea-group.com
www.bea-group.com

BeA is a member of the following trade associations:

